

Staging Dimensions SD 5000

Specifications

Standard Deck Size: 4' x 8' x 3 3/4"

Frame Extrusion: Aluminum tube extrusion frame made from 6105-T5 extruded aluminum. Tube construction offers superior strength but is lightweight.

Corner Extrusion: Each corner is a separate aluminum extrusion made from 6105-T5 extruded aluminum. Having a separate corner allows for replacement in minutes should the corners ever become damaged if deck is dropped.

Hardware: All Staging Dimensions decks are assembled with Grade 5 zinc plated bolts, Nylock nuts and screws.

Center Brace: Each 4' x 8' deck has an additional center brace support for additional strength running the 8' length centered at the 2' mark.

Dual Locks: Dual Lock™ butt-joint cam-type coffin locks offer 2500 pound tensile strength. Each 4' x 8' deck has three male and three female locks to accommodate locking each deck together. The male Dual Lock™ can be activated from the top or the bottom of the deck.

Deck Surface: The SD5000 portable stage deck is available in a variety of deck surfaces. The choices are unfinished plywood, finished plywood, Plyron hardboard, Hair Cell polyvinyl, Quad Ripple polyvinyl, and carpet. Custom surfaces are available per your specifications.

Velcro: Each SD5000 portable stage deck comes standard with black hook Velcro ready to accept your choice of skirting. The frame extrusion has our exclusive slot design engineered into the frame to accept hook Velcro so it can't be torn or damaged when assembling or transporting the decks.

Point Load: The SD5000 portable stage deck has an allowable live load capacity of 200psf and weighs less than 140 pounds. Compare that with the competition and you will see that Staging Dimensions leads the pack.